

# Trimble R12i

## GNSS SYSTEM

### KEY FEATURES

- ▶ Trimble® Inertial Platform™ (TIP™) technology. Calibration-free and magnetically immune IMU-based tilt compensation for topo measurements and stakeout.
- ▶ Trimble ProPoint® GNSS positioning engine. Engineered for improved accuracy and productivity in challenging GNSS conditions.
- ▶ 672-channel solution with Trimble 360 satellite tracking technology
- ▶ Trimble CenterPoint® RTX correction service delivers fast, RTK level accuracy worldwide via satellite/IP
- ▶ Trimble xFill® correction outage technology
- ▶ Trimble IonoGuard™ technology for mitigation of ionospheric GNSS signal disruptions
- ▶ Optimized for Trimble Access™ field software
- ▶ Android™ and iOS platform support
- ▶ Cellular, Bluetooth®, Wi-Fi® data connectivity
- ▶ Military-spec rugged design and IP-67 rating
- ▶ Ergonomic form factor
- ▶ All day battery with built-in status indicator
- ▶ 6 GB internal memory

**Learn more:**  
[geospatial.trimble.com/r12i](https://geospatial.trimble.com/r12i)



Tilt  
Compensation

## PERFORMANCE SPECIFICATIONS

## GNSS MEASUREMENTS

|                                                                                                                                                                                                                                                                                                             |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Constellation agnostic, flexible signal tracking, improved positioning in challenging environments <sup>1</sup> and inertial measurement integration with Trimble ProPoint GNSS technology.                                                                                                                 |
| Increased measurement and stakeout productivity and traceability with Trimble TIP technology IMU-based tilt compensation                                                                                                                                                                                    |
| Advanced Trimble Custom Survey GNSS chips with 672 channels                                                                                                                                                                                                                                                 |
| Trimble CenterPoint RTX correction service is activated and ready to use for the initial 12 months.<br>Learn more at <a href="https://rtx.trimble.com">rtx.trimble.com</a>                                                                                                                                  |
| Reduced downtime due to loss of radio signal or cellular connectivity with Trimble xFill technology                                                                                                                                                                                                         |
| Trimble IonoGuard technology for mitigation of ionospheric GNSS signal disruptions                                                                                                                                                                                                                          |
| Signals tracked simultaneously                                                                                                                                                                                                                                                                              |
| GPS: L1C, L1C/A, L2C, L2E, L5<br>GLONASS: L1C/A, L1P, L2C/A, L2P, L3<br>SBAS (WAAS, EGNOS, GAGAN, MSAS): L1C/A, L5<br>Galileo: E1, E5A, E5B, E5 AltBOC, E6 <sup>2</sup><br>BeiDou: B1, B1C, B2, B2A, B2B, B3<br>QZSS: L1C/A, L1S, L1C, L2C, L5, L6<br>NavIC (IRNSS): L5<br>L-band: Trimble RTX® Corrections |
| Iridium filtering above 1616 MHz allows antenna to be used up to 20 m away from iridium transmitter                                                                                                                                                                                                         |
| Japanese LTE filtering below 1510 MHz allows antenna to be used up to 100 m away from Japanese LTE cell tower                                                                                                                                                                                               |
| Digital Signal Processor (DSP) techniques to detect and recover from spoofed GNSS signals                                                                                                                                                                                                                   |
| Advanced Receiver Autonomous Integrity Monitoring (RAIM) algorithm to detect and reject problem satellite measurements to improve position quality                                                                                                                                                          |
| Improved protection from erroneous ephemeris data                                                                                                                                                                                                                                                           |
| Positioning Rates                                                                                                                                                                                                                                                                                           |
| 1 Hz, 2 Hz, 5 Hz, 10 Hz, and 20 Hz                                                                                                                                                                                                                                                                          |

POSITIONING PERFORMANCE<sup>3</sup>

## STATIC GNSS SURVEYING

## High-Precision Static

|            |                      |
|------------|----------------------|
| Horizontal | 3 mm + 0.1 ppm RMS   |
| Vertical   | 3.5 mm + 0.4 ppm RMS |

## Static and Fast Static

|            |                    |
|------------|--------------------|
| Horizontal | 3 mm + 0.5 ppm RMS |
| Vertical   | 5 mm + 0.5 ppm RMS |

## REAL TIME KINEMATIC SURVEYING

## Single Baseline &lt;30 km

|            |                   |
|------------|-------------------|
| Horizontal | 8 mm + 1 ppm RMS  |
| Vertical   | 15 mm + 1 ppm RMS |

Network RTK<sup>4</sup>

|            |                     |
|------------|---------------------|
| Horizontal | 8 mm + 0.5 ppm RMS  |
| Vertical   | 15 mm + 0.5 ppm RMS |

RTK start-up time for specified precisions<sup>5</sup>

|                |
|----------------|
| 2 to 8 seconds |
|----------------|

## TRIMBLE INERTIAL PLATFORM (TIP) TECHNOLOGY

TIP Compensated Surveying<sup>6</sup>

|            |                                             |
|------------|---------------------------------------------|
| Horizontal | RTK + 3 mm + 0.15 mm/° tilt (up to 40°) RMS |
| Horizontal | RTX + 3 mm + 0.15 mm/° tilt (up to 40°) RMS |

## IMU Integrity Monitor

|                 |                            |
|-----------------|----------------------------|
| Bias monitoring | Temperature, age and shock |
|-----------------|----------------------------|

## TRIMBLE RTX CORRECTION SERVICES

CenterPoint RTX<sup>7</sup>

|                                                                           |          |
|---------------------------------------------------------------------------|----------|
| Horizontal                                                                | 2 cm RMS |
| Vertical                                                                  | 3 cm RMS |
| RTX convergence time for specified precisions in Trimble RTX Fast regions | < 1 min  |
| RTX convergence time for specified precisions in non RTX Fast regions     | < 15 min |
| RTX QuickStart convergence time for specified precisions                  | < 1 min  |

TRIMBLE xFILL<sup>8</sup>

|            |                                     |
|------------|-------------------------------------|
| Horizontal | RTK <sup>9</sup> + 10 mm/minute RMS |
| Vertical   | RTK <sup>9</sup> + 20 mm/minute RMS |

TRIMBLE xFILL PREMIUM<sup>8</sup>

|            |          |
|------------|----------|
| Horizontal | 3 cm RMS |
| Vertical   | 7 cm RMS |

## CODE DIFFERENTIAL GNSS POSITIONING

|                    |                      |
|--------------------|----------------------|
| Horizontal         | 0.25 m + 1 ppm RMS   |
| Vertical           | 0.50 m + 1 ppm RMS   |
| SBAS <sup>10</sup> | typically <5 m 3DRMS |

# Trimble R12i GNSS SYSTEM

## HARDWARE

### PHYSICAL

|                                                                              |                                                                                                                                                               |                                                                                                                     |
|------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Dimensions (W×H)                                                             | 11.9 cm x 13.6 cm (4.6 in x 5.4 in)                                                                                                                           |                                                                                                                     |
| Weight                                                                       | 1.12 kg (2.49 lb) with internal battery, internal radio with UHF antenna,<br>3.95 kg (8.71 lb) items above plus range pole, Trimble TSC7 controller & bracket |                                                                                                                     |
| Temperature <sup>11</sup>                                                    |                                                                                                                                                               |                                                                                                                     |
|                                                                              | Operating                                                                                                                                                     | -40 °C to +65 °C (-40 °F to +149 °F)                                                                                |
|                                                                              | Storage                                                                                                                                                       | -40 °C to +75 °C (-40 °F to +167 °F)                                                                                |
| Humidity                                                                     | 100%, condensing                                                                                                                                              |                                                                                                                     |
| Ingress protection                                                           | IP67 dustproof, protected from temporary immersion to depth of 1 m (3.28 ft)                                                                                  |                                                                                                                     |
| Shock and vibration (Tested and meets the following environmental standards) |                                                                                                                                                               |                                                                                                                     |
|                                                                              | Shock                                                                                                                                                         | Non-operating: Designed to survive a 2 m (6.6 ft) pole drop onto concrete.<br>Operating: to 40 G, 10 msec, sawtooth |
|                                                                              | Vibration                                                                                                                                                     | MIL-STD-810F, FIG.514.5C-1                                                                                          |

### ELECTRICAL

|                                                   |                                                                                                         |           |
|---------------------------------------------------|---------------------------------------------------------------------------------------------------------|-----------|
|                                                   | Power 11 to 24 V DC external power input with over-voltage protection on Port 1 and Port 2 (7-pin Lemo) |           |
|                                                   | Rechargeable, removable 7.4 V, 3.7 Ah Lithium-ion smart battery with LED status indicators              |           |
|                                                   | Power consumption is 4.2 W in RTK rover mode with internal radio <sup>12</sup>                          |           |
| Operating times on internal battery <sup>13</sup> |                                                                                                         |           |
|                                                   | 450 MHz receive only option                                                                             | 6.5 hours |
|                                                   | 450 MHz receive/transmit option (0.5 W)                                                                 | 6.0 hours |
|                                                   | 450 MHz receive/transmit option (2.0 W)                                                                 | 5.5 hours |
|                                                   | Cellular receive option                                                                                 | 6.5 hours |

## COMMUNICATIONS AND DATA STORAGE

|                                                         |                                                                                                                                                                                                                               |                                              |
|---------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|
| Serial                                                  | 3-wire serial (7-pin Lemo)                                                                                                                                                                                                    |                                              |
| USB v2.0                                                | Supports data download and high speed communications                                                                                                                                                                          |                                              |
| Radio modem                                             | Fully Integrated, sealed 450 MHz wide band receiver/transmitter with frequency range of 403 MHz to 473 MHz, support of Trimble, Pacific Crest, and SATEL radio protocols:                                                     |                                              |
|                                                         | Transmit power                                                                                                                                                                                                                | 2 W                                          |
|                                                         | Range                                                                                                                                                                                                                         | 3–5 km typical / 10 km optimal <sup>14</sup> |
| Cellular <sup>15</sup><br>(not available in all models) | Integrated, 3.5 G modem, HSDPA 7.2 Mbps (download), GPRS multi-slot class 12, EDGE multi-slot class 12, Penta-band UMTS/ HSDPA (WCDMA/FDD) 800/850/900/1900/2100 MHz, Quad-band EGSM 850/900/1800/1900 MHz, GSM CSD, 3GPP LTE |                                              |
| Bluetooth                                               | Version 4.1 <sup>16</sup>                                                                                                                                                                                                     |                                              |
| Wi-Fi                                                   | 802.11 b,g, access point and client mode, WPA/WPA2/WEP64/WEP128 encryption                                                                                                                                                    |                                              |
| I/O ports                                               | Serial, USB, TCP/IP, IBSS/NTRIP, Bluetooth                                                                                                                                                                                    |                                              |
| Data storage                                            | 6 GB internal memory                                                                                                                                                                                                          |                                              |
| Data format                                             | CMR+, CMRx, RTCM 2.1, RTCM 2.3, RTCM 3.0, RTCM 3.1, RTCM 3.2 input and output<br>24 NMEA outputs, GSOF, RT17 and RT27 outputs                                                                                                 |                                              |

### WEBUI

|  |                                                                   |  |
|--|-------------------------------------------------------------------|--|
|  | Offers simple configuration, operation, status, and data transfer |  |
|  | Accessible via Wi-Fi, Serial, USB, and Bluetooth                  |  |

### SUPPORTED CONTROLLERS & FIELD SOFTWARE

|  |                                                                                                                           |  |
|--|---------------------------------------------------------------------------------------------------------------------------|--|
|  | Trimble TSC7, Trimble T10, Trimble T7, Android and iOS devices running supported apps                                     |  |
|  | Trimble Access 2020.10 or later, Trimble TerraFlex® software                                                              |  |
|  | Supports Trimble Internet Base Station Service (IBSS) for streaming RTK corrections using Trimble Access 2023.10 or later |  |

## CERTIFICATIONS

|  |                                                                   |  |
|--|-------------------------------------------------------------------|--|
|  | FCC Part 15 (Class B device), 24, 32; CE Mark; RCM; PTCRB; BT SIG |  |
|--|-------------------------------------------------------------------|--|



- 1 Challenging GNSS environments are locations where the receiver has sufficient satellite availability to achieve minimum accuracy requirements, but where the signal may be partly obstructed by and/or reflected off of trees, buildings, and other objects. Actual results may vary based on user's geographic location and atmospheric activity, scintillation levels, GNSS constellation health and availability, and level of multipath and signal occlusion.
- 2 The current capability in the receivers is based on publicly available information. As such, Trimble cannot guarantee that these receivers will be fully compatible with a future generation of Galileo satellites or signals.
- 3 Precision and reliability may be subject to anomalies due to multipath, obstructions, satellite geometry, and atmospheric conditions. The specifications stated recommend the use of stable mounts in an open sky view, EMI and multipath clean environment, optimal GNSS constellation configurations, along with the use of survey practices that are generally accepted for performing the highest-order surveys for the applicable application including occupation times appropriate for baseline length. Baselines longer than 30 km require precise ephemeris and occupations up to 24 hours may be required to achieve the high precision static specification.
- 4 Network RTK PPM values are referenced to the closest physical base station.
- 5 May be affected by atmospheric conditions, signal multipath, obstructions and satellite geometry. Initialization reliability is continuously monitored to ensure highest quality.
- 6 TIP references the overall positioning error estimate at the tip of the surveying pole throughout the tilt compensation range. RTK refers to the estimated horizontal precision of the underlying GNSS position, which is dependent on factors that affect GNSS solution quality. The 3 mm constant error component accounts for residual misalignment between the vertical axes of the receiver and the built-in Inertial Measurement Unit (IMU) after factory calibration, assuming the receiver is mounted on a standard 2 m carbon fiber range pole which is properly calibrated and free from physical defects. The tilt-dependent error component is a function of the quality of the computed tilt azimuth, which is assumed here to be aligned using optimal GNSS conditions. To achieve  $\pm 3 \text{ mm} + 0.15 \text{ mm}/^\circ$  tilt (up to  $40^\circ$ ) RMS tilt spec, firmware version 6.43 or later is required.
- 7 RMS performance based on repeatable in field measurements. Achievable accuracy and initialization time may vary based on type and capability of receiver and antenna, user's geographic location and atmospheric activity, scintillation levels, GNSS constellation health and availability and level of multipath including obstructions such as large trees and buildings.
- 8 Accuracies are dependent on GNSS satellite availability. xFill positioning without an xFill Premium subscription ends after 5 minutes of radio downtime. xFill Premium will continue beyond 5 minutes providing the solution has converged, with typical precisions not exceeding 3 cm horizontal, 7 cm vertical. xFill is not available in all regions, check with your local sales representative for more information.
- 9 RTK refers to the last reported precision before the correction source was lost and xFill started.
- 10 Depends on SBAS system performance.
- 11 Receiver will operate normally to  $-40^\circ\text{C}$ , internal batteries are rated from  $-20^\circ\text{C}$  to  $+60^\circ\text{C}$  (ambient  $+50^\circ\text{C}$ ).
- 12 Tracking GPS, GLONASS and SBAS satellites.
- 13 Varies with temperature and wireless data rate. When using a receiver and internal radio in the transmit mode, it is recommended that an external 6 Ah or higher battery is used.
- 14 Varies with terrain and operating conditions.
- 15 Due to local regulations, the integrated cellular modem cannot be enabled in China, Taiwan, or Brazil. A Trimble controller integrated cellular modem or external cellular modem can be used to obtain GNSS corrections via an IP (Internet Protocol) connection.
- 16 Bluetooth type approvals are country specific.

Specifications subject to change without notice.



**FRONTIER PRECISION**  
GEOSPATIAL

sales@frontierprecision.com  
www.frontierprecision.com/solutions/geospatial

Contact your local Trimble Authorized Dealer  
for more information

#### NORTH AMERICA

Trimble Inc.  
10368 Westmoor Dr  
Westminster CO 80021  
USA

#### EUROPE

Trimble Germany GmbH  
Am Prime Parc 11  
65479 Raunheim  
GERMANY

#### ASIA-PACIFIC

Trimble Navigation  
Singapore PTE Limited  
3 HarbourFront Place  
#13-02 HarbourFront Tower Two  
Singapore 099254  
SINGAPORE

© 2020–2025, Trimble Inc. All rights reserved. Trimble, the Globe & Triangle logo, CenterPoint, ProPoint, TerraFlex, Trimble RTX and xFill are trademarks of Trimble Inc., registered in the United States and in other countries. IonoGuard, Trimble Access, Trimble Inertial Platform and TIP are trademarks of Trimble Inc. iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. Google, Google Play, Android and other marks are trademarks of Google LLC. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Inc. is under license. Galileo is developed under a License of the European Union and the European Space Agency. All other trademarks are the property of their respective owners. PN 022516-511H (07/25)